


This 1" - 4 single lead acme machine screw is available in both alloy steel and stainless steel with a corresponding aluminum bronze nut. Choose from right-hand or left-hand threads.

MACHINE SCREW SPECIFICATIONS	RH	LH	
ALLOY STEEL SCREW NO.	AS 100 R 025 A	AS 100 L 025 A	
STAINLESS STEEL SCREW NO.	AS 100 R 025 S	A S100 L 025 S	
THREAD FORM		ACME	
SCREW DIAMETER - TURNS / INCH		1-4	
PITCH / LEAD		0.250 IN.	
ROOT DIAMETER		0.699 IN.	
SCREW WEIGHT (LB./FT.)		2.2	
TORQUE TO RAISE 1 POUND		0.097 INLB.	
MAXIMUM SCREW LENGTH		12 FEET	

Nut and Flange Specifications



NUT SPECIFICATIONS	RH	LH
NUT PART NO.	AN 100 R 025 B	AN 100 L 025 B
NUT WITH FLANGE PART NO.	AF 100 R 025	AF 100 L 025
DYNAMIC LOAD CAPACITY (LBS.)	5,000	
STATIC LOAD CAPACITY (LBS.)	16,000	
EFFICIENCY	41.9%	
MATERIAL	BRONZE	
NOMINAL DIAMETER "A"	1.50 IN.	
NUT LENGTH "B"	1.50 IN.	
THREAD LENGTH "C"	0.50 IN.	
THREAD SIZE	1.375-16 UN	
FLANGE PART NUMBER	FL-1375	
FLANGE DIAMETER "D"	2.75 IN.	
FLANGE THICKNESS "E"	0.52 IN.	
FLANGE HOLE DIAMETER "F"	0.266 IN.	
NUMBER OF HOLES IN FLANGE "G"	4	
FLANGE BOLT CIRCLE "H"	2.260 IN.	
FLANGE MATERIAL	BLACK OXIDE COATED STEEL	