INTEGRATED ACTUATORS

250-2000 POUND INTEGRATED ACME SCREW

IA 51TT / DIA 51TT IA 201TT / DIA 201TT



Model Number		IA51TT		DIA51TT	
		IA201TT		DIA201TT	
ACME Threaded Lifting Screw		1" diameter .25" pitch		1" diameter .25" pitch .50" lead	
Wormgear Ratio		5:1		5:1	
		20:1		20:1	
Worm Shaft Turns/1" Travel		20		10	
		80		40	
Motor RPM		1140	1725	1140	1725
Lifting Speed (Inches/Minute)		57	86	114	172
		14	21	28	43
Rated Loads (Lbs.)	1/3 HP Motor	550	375	375	250
		1775	1225	1250	850
	1/2 HP Motor	850	550	575	400
		2000	1850	1875	1300
	3/4 HP Motor	1250	850	875	600
		2000	2000	2000	1950

Lead: The distance traveled axially in one rotation of the lifting screw.

Pitch: The distance from a point on a screw thread to a corresponding point on the next thread, measured axially.

Important Note: DIA models may lower under load. Brake motors or external locking systems are recommended.



Note: Drawings are artist's conception - not for certification; dimensions are subject to change without notice.

INTEGRATED ACTUATORS

250-2000 POUND INTEGRATED ACME SCREW







Model Number		IA51TN		DIA51TN*	
		IA201TN		DIA201TN*	
ACME Threaded Lifting Screw		1" diameter .25" pitch		1" diameter .25" pitch .50" lead	
Wormgear Ratio		5:1		5:1	
		20:1		20:1	
Worm Shaft Turns/1" Travel		20		10	
		80		40	
Motor RPM		1140	1725	1140	1725
Lifting Speed Inches/Minute		57	86	114	172
		14	21	28	43
Rated Loads (Lbs.)	1/3 HP Motor	550	375	375	250
		1775	1225	1250	850
	1/2 HP Motor	850	550	575	400
		2000	1850	1875	1300
	3/4 HP Motor	1250	850	875	600
		2000	2000	2000	1950

Lead: The distance traveled axially in one rotation of the lifting screw.

Pitch: The distance from a point on a screw thread to a corresponding point on the next thread, measured axially.

Important Note: *DIA models may lower under load. Brake motors or external locking systems are recommended.

Note: Drawings are artist's conception - not for certification; dimensions are subject to change without notice.